

"CHROMALAC"- SYNTHETIC ENAMEL GLOSSY PAINT

PRODUCT DESCRIPTION:

Alkyd based general purpose synthetic enamel. It is durable & resistance to moderate atmosphere. It is dries to give gloss finish. It also has excellent weather resistance.

USES:

Suitable for interior and exterior surfaces. Apply on metal surface and wood surface. Apply 1st coat suitable primer on base surface then apply this enamel paint 2 coat.

SURFACE PREPARATION:

Remove grease, oil and others contaminants and Blast clean to SA 21/2 grade minimum of Swedish Specification. The surface should be clear and dry before application.

PRECAUTIONS:

Not to be applied when the temperature is above 50°C and relative humidity rises 90%. Do not apply during the rain & fog or mist.

METHOD OF APPLICATION:

Airless spray, conventional spray & by brush.

TYPE

Single pack. Air drying.

RECOMMENDED DFT:

40 - 50 Microns (Minimum).

DRYING TIME:

Surface Dry: Within 4-6 Hours.

Dry to Recoat: 18 hours

Hard Dry: 24 HOURS.

THEORETICAL SPREADING RATE:

11-13.75 M²/ltr/coat

FLASH POINT:

Above 30⁰ C

SPECIFIC GRAVITY

1.05 ± 0.5

COLOUR:

Yellow, Green and any suitable colour.

THINNER:

Recommended Spl. NDC thinner

SHELF LIFE:

One year from the date of mfg.

PACKING

20 ltr & 4 Ltr

DISCLAIMER: The information given in this data sheet is best of our knowledge, observed while tested in ideal condition in our laboratory.

WORKS: POST & VILL & PO: BAMUNARI, NH -2, DELHI ROAD .DIST HOOGHLY, 712205, WEST BENGAL. PHONE: 9830317320

OFFICE: JEEVAN NIWAS, 30A, BLOCK -R, NEW ALIPORE, 2ND FLOOR, FLAT A/5
KOLKATA: 700 053,
CONTACT: +91 9830848300 / 98308 49200 / 9674129944.